



Ref. Certif. No.

ES2525-AENOR

**IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME**

CB TEST CERTIFICATE

Product

FIXED GENERAL PURPOSE LUMINAIRES

Name and address of the applicant

ZALUX, S.A.
CENTRO EMPRESARIAL MIRALBUENO. AVENIDA MANUEL
RODRÍGUEZ AYUSO, 114 - PLANTA 1ª LOCAL P-2
50012 ZARAGOZA (Spain)

Name and address of the manufacturer

ZALUX, S.A.
AV ARAGÓN, 54
50230 ALHAMA DE ARAGÓN (Zaragoza - Spain)

Name and address of the factory

SAME AS ABOVE

Note: When more than one factory, please report on page 2

Additional Information on page 2

Ratings and principal characteristics

See Annex

Trademark (if any)

ZALUX

Customer's Testing Facility (CTF) Stage used

-

Model / Type Ref.

See references on the Annex

Additional information (if necessary may also be reported on page 2)

Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 60598-1:2020
IEC 60598-2-1:2020
IEC 60598-2-24:2013

As shown in the Test Report Ref. No. which forms part of this Certificate

2021100545B1

This CB Test Certificate is issued by the National Certification Body

AENOR INTERNACIONAL S.A.U.
CI Génova, 6
ES-28004 MADRID (SPAIN)

Date: 2022-01-18


Signature: Rafael GARCÍA MEIRO
Chief Executive Officer

ANNEX TO CB CERTIFICATE N° ES2525-AENOR

CERTIFIED REFERENCES AND THEIR PRINCIPAL CHARACTERISTICS

Product: FIXED GENERAL PURPOSE LUMINAIRES
Trade Mark: ZALUX

Type reference	Rated voltage and frequency	N° of lamps and rated wattage	Type of lamps and lampholder	Degree of protection (IP)	Power supply connection means	Class. respect supporting material	Protection against electric shock (class)	Limitations	Additional data
KHE 1.2	220-240 V~; 0-50/60 Hz	14 - 30 W	LED module (SMD)	IP 66 + IPX9 (80 °C)	Terminals / connectors	Suitable for normally flammable surfaces	Class I	Horizontal fixing; ta = 55 °C max	KHE Series, 1200 mm; cool, neutral and warm white
KHE 1.5	220-240 V~; 0-50/60 Hz	16 - 64 W	LED module (SMD)	IP 66 + IPX9 (80 °C)	Terminals / connectors	Suitable for normally flammable surfaces	Class I	Horizontal fixing; ta = 55 °C max	KHE Series, 1500 mm; cool, neutral and warm white